

PRODUCT MODEL : ULTRA20-PC2M(P) / ULTRA20-PC2M(Q)
PRODUCT NUMBER : DEM-POU20-01P / DEM-POU20-01Q

Specification:



- ◆ **System (Model)**
ULTRA20-PC2M(P) → PVC PIPE
ULTRA20-PC2M(Q) → QUICK CONNECT
- ◆ **Connection/Pipe**
½” push fittings / 1” SCH80 connection
- ◆ **Filter Housing Material**
Stainless Steel 304
- ◆ **System Dimensions**
545 x 270 x 730 mm (LxWxH) PVC
545 x 270 x 700 mm (LxWxH) QUICK CONNECT
- ◆ **System Weight (fully-filled)**
Approx. 17.5 kg PVC
16.5 kg QUICK CONNECT
- ◆ **Filters Life*** Up to 12 months for pre-filter and 18months for membrane
- ◆ **Membrane material**
GO-modified PES ultrafiltration membrane with enhanced hydrophilicity and antifouling properties
- ◆ **Pore Size** <100,000 Da
- ◆ **Rated service flow (LPM)**
≥ 15 LPM at 30°C (1 bar) **
- ◆ **Operating Pressure**
< 3 bar (30psi)
- ◆ **Operating Temperature**
5°C – 40°C
- ◆ **Replacement Filter (Model)**
UltraGO-4020 (Membrane)
PP2520, CTO2520 (Pre-filters)

* Filter life dependent on usage and overall incoming water quality

** Manufacturer-certified for quality and performance

For customisation, please contact us for discussion.

Packaging information:

Dimension: 765 x 495 x 350 mm (LxWxH)

Weight: 20.5 kg PVC, 19.5 kg QUICK CONNECT

Applications: provide high flow rate to support demand for clean drinking water
In large households/apartments/condominiums and small businesses, hotels.