

**PRODUCT MODEL : ULTRAGO-4020H**  
**PRODUCT NUMBER : DEM-SS4020-01**

**Specification:**



- ◆ **Connection/Pipe**  
BSPT ½” Female Adaptors
- ◆ **Housing Material**  
Stainless Steel 304
- ◆ **System Dimensions**  
458 x127 x 127 mm
- ◆ **System Weight (fully filled)**  
Approx. 5.5kg
- ◆ **Filter Life\*** Up to 18 months
- ◆ **Membrane area** 2.0 m<sup>2</sup>
- ◆ **Membrane material**  
GO-modified PES membrane with enhanced hydrophilicity and antifouling properties
- ◆ **Pore Size** <100,000 Da
- ◆ **Rated service flow (LPM)**  
2.6 GPM at 22°C (60 psi)^  
≥ 7.5 LPM at 30°C (1 bar) \*\*
- ◆ **Certifications**  
NSF/ANSI Standards 53,  
Global-Mark AS4020,  
AS3497
- ◆ **Operating Pressure**  
< 3 bar (43psi)
- ◆ **Operating Temperature**  
5°C – 40°C
- ◆ **Replacement Filter (Model)**  
UltraGO-4020

\* Filter life dependent on usage and overall incoming water quality

\*\* Manufacturer-certified for quality and performance

^ NSF-certified

**Packaging information:**

Individual cartridges will be packed in a carton box.

Dimension: 517 mm X 165 mm X 165 mm (LxWxH)

Weight: Approx. 5.9kg

**Applications:** Drinking water filtration, point-of-use systems, residential / light commercial use (with pre-filters).